



Flame Retardant fabric for FR-clothing

Madeira-260

100% COTTON

260 GSM / TWILL 3/1



Fabric name	Madeira-260
Fabric weight	260 g/m
Composition	100% Cotton
Full width	152 cm
Weave	Twil 3/1
Finishes	Flame Retardant
Application	Welders jackets, trousers and coveralls
Washing instruction	

FR & SPECIAL PROPERTIES

Flame retardant	EN ISO 11612 A1 & A2, B1, C1, E2, F1	EN ISO 11611 Class 1
-----------------	--------------------------------------	----------------------

PHYSICAL PROPERTIES

		Warp	Weft
Tensile strength, N	ISO 13934-1:1999	1200 N	550 N
Tearing strength, N	ISO 13937-2:2000	32 N	30 N
Dimensional Stability To Washing, max	ISO 5077-ISO 15797	3%	
Abrasion Resistance	ISO 12947-2:1999	20,0 rubs	
Pilling Resistance	ISO 12945-2:2001	3-4	

COLOUR FASTNESS

			Light	Mid	Dark	Special colors
			Orange, Yellow, Red	Green, Grey, Royal Box	Dark Navy, Navy, Royal Blue	Black
Wash Fastness Method E2S (95°C)	ISO 105-C06	Colour Change	4-5	4-5	4-5	4
		Stain on Polyester	4-5	4-5	4-5	4
		Stain on Cotton	4	4	4-5	3-4
Rub Fastness	ISO 105-X12:1995	Wet	3	3	2-3	2
		Dry	4	4	4	4
Light Fastness	ISO 105-B02		3	4	4	4

XM Textiles Europe

Email: info@xmtextiles.com
www.xmtextiles.com

Darius ir Gireno st. 42A Office 509
Vilnius LT – 02189 Lithuania
Tel: +370 (347) 20299

Sos.Tamasi 20, Hala 3A, et. 1
Buftea (platforma Rombiz), Romania
Zip 070000, Tel: +40 31 630 36 39